

Agricultural Area Fence Section

قسم سياج المناطق الزراعية

FINISH	NOTES										
<p>CLASS-2</p> <ol style="list-style-type: none"> Setted tension after the H.T. wire is strained shall be 140kg. Tension for each cable must develop a spring rate of 80— 9 kg/cm. All fittings and bolts needed to connect cables to anchor blocks shall be compatible TO CABLE Strength and Size. Straining posts, braces and fittings shall be hot dipped galvanized in accordance to ASTM-A223-B1 After fabrication. 											
<p>INTERMEDIATE POST MEDIAN</p>	<p>MANUFACTURE: مصنع تيك و جي للتنمية الالكترونية Hi-Tech Fence & Steel Industries</p>										
<p>STRAINING POST</p>	<p>FENCE TYPE: AGRICULTURAL AREA FENCE SECTION</p> <table border="1"> <tr> <td>DESIGN: MOZ</td> <td>SCALE: AS SHOWN</td> </tr> <tr> <td>DRAWN: 10/07/13</td> <td>DATE: 10/07/13</td> </tr> <tr> <td>CHECKED: MO</td> <td>DRG. NO.: A</td> </tr> <tr> <td>APPROVED: MO</td> <td>REF.: A</td> </tr> <tr> <td colspan="2">AGRICULTURAL AREA FENCE SECTION</td> </tr> </table>	DESIGN: MOZ	SCALE: AS SHOWN	DRAWN: 10/07/13	DATE: 10/07/13	CHECKED: MO	DRG. NO.: A	APPROVED: MO	REF.: A	AGRICULTURAL AREA FENCE SECTION	
DESIGN: MOZ	SCALE: AS SHOWN										
DRAWN: 10/07/13	DATE: 10/07/13										
CHECKED: MO	DRG. NO.: A										
APPROVED: MO	REF.: A										
AGRICULTURAL AREA FENCE SECTION											
<p>INTERMEDIATE POSTS</p>	<p>INTERMEDIATE STRAINING POST STRUT CONNECTION AND RATCHET WINDER</p>										